

1. Features

- Typical 1dB bandwidth of 9.8 MHz
- High attenuation
- Single Ended Operation
- Dual In-line Package (DIP)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications


Source and Load Impedance = 50Ω

Operating Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	57.6	-
Insertion Loss	dB	-	24.3	26.0
1dB Bandwidth	MHz	9.6	9.8	-
3dB Bandwidth	MHz	-	10.15	-
40dB Bandwidth	MHz	-	12.0	12.1
Amplitude Ripple (fo ± 4.6 MHz)	dB	-	0.5	1.0
Group Delay Variation (fo ± 4.6 MHz)	nsec	-	25	60
Absolute Delay	usec	-	1.86	1.9
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-72		

D2012 Package Dimension



Matching Schematic



Unmatching required

Pin Configuration

	1	Ground	2,4
Input	1	Ground	2,4
Output	5	Others	Ground

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

3. Typical Performance (at +25°C)

