


SAW Bandpass Filter 201136B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters
 Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201136B	
		Rev. Date	2004-11-02	
		Rev.	DS4058-CS01	1/5

SAW Bandpass Filter 201136B



3. Specifications

Fo = 70.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	69.94	70.0	70.06
Insertion Loss	dB	-	21.0	23.0
1dB Bandwidth	MHz	-	8.3	-
3dB Bandwidth	MHz	8.5	8.85	-
40dB Bandwidth	MHz	-	10.85	11.0
Amplitude Ripple (Fo +/-3.8 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 3.8 MHz)	nsec	-	80	150
Absolute Delay	usec	-	2.32	-
Ultimate Rejection	dB	50	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-94	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201136B	
		Rev. Date	2004-11-02	
		Rev.	DS4058-CS01	2/5

SAW Bandpass Filter 201136B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)




L1 = 270nH, L2=270nH

5. Marking Configuration

ITF¹⁾04A001²⁾
201136B³⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	201136B	
		Rev. Date	2004-11-02	
		Rev.	DS4058-CS01	3/5

SAW Bandpass Filter 201136B



6. Typical Performance (at +25°C)



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.

201136B

Rev. Date





2004-11-02

Rev.

DS4058-CS01

4/5

SAW Bandpass Filter 201136B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No. 201136B

Rev. Date 2004-11-02

Rev. DS4058-CS01 5/5