


Bandpass Filter 222103B



1. Features

- IF bandpass filter
- Low-Loss Filter
- Single-ended operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012


Pin Configuration	
1	Input
4	Output
Other	ground

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu and Cr Alloy, Ni plated

Terminations : Kover, Au plated

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	222103B	
		Rev. Date	2006-09-05	
		Rev.	NJ6015-CS02	1/5

Bandpass Filter 222103B



3. Specifications


Fo =60.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

Operating temperature range : -10℃ ~ +70℃		Minimum	Typical	Maximum
Center Frequency	MHz	-	60.0	-
Insertion Loss	dB	-	14.5	17.0
1dB Bandwidth	MHz	20.0	20.7	-
3dB Bandwidth	MHz		21.5	-
40dB Bandwidth	MHz	-	24.8	25.0
Amplitude Ripple (Fo +/- 9.75MHz)	dB	-	0.6	1.0
Group Delay Variation (Fo +/- 9.75 MHz)	nsec	-	40	80
Absolute Delay	usec	-	1.29	-
Ultimate Rejection	dB	40	45	
Temperature Coefficient of Frequency	ppm/°C	-	-86	-

Room temperature : + 25℃		Minimum	Typical	Maximum
Center Frequency	MHz	-	60.0	-
Insertion Loss	dB	-	14.5	16.5
Amplitude Ripple (Fo +/- 10.0 MHz)	dB	-	0.6	1.0
Group Delay Variation (Fo +/- 10.0 MHz)	nsec	-	40	80

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	222103B	
		Rev. Date	2006-09-05	
		Rev.	NJ6015-CS02	2/5

Bandpass Filter 222103B




Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration
- 3) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 4) All attenuation measurements are measured relative to insertion loss

4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$$L1 = L4 = 100\text{nH}$$
$$L2 = 180\text{ nH}, \quad L3 = 220\text{nH}$$

5. Marking Configuration

ITF¹⁾06A001²⁾
222103B³⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	222103B	
		Rev. Date	2006-09-05	
		Rev.	NJ6015-CS02	3/5

Bandpass Filter 222103B



6. Typical Performance (at +25°C)







ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No. 222103B

Rev. Date 2006-09-05

Rev. NJ6015-CS02 4/5

Bandpass Filter 222103B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	222103B	
Rev. Date	2006-09-05	
Rev.	NJ6015-CS02	5/5