

1. Features

- Typical 1dB bandwidth of 32.4 MHz
- High attenuation
- Single Ended Operation
- Surface Mounted Package (SMD)

RoHS Compliant

Tested by SGS Testing Korea


2. Electrical Specifications

Source and Load Impedance = 50Ω

Operating Temperature : -10℃ ~ +60℃		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	75.0	-
Insertion Loss	dB	-	16.5	19.0
1dB Bandwidth	MHz	31.9	32.4	-
3dB Bandwidth	MHz	-	33.45	-
40dB Bandwidth	MHz	-	38.5	39.0
Amplitude Ripple (fo ± 14.5 MHz)	dB	-	0.45	1.0
Group Delay Variation (fo ± 14.5 MHz)	nsec	-	15	50
Absolute Delay	usec	-	0.88	-
Ultimate Rejection	dB	40	45	-
Temperature Coefficient of Frequency	ppm/℃	-	-86	-

Operating Temperature : +25℃		Minimum	Typical	Maximum
Insertion Loss	dB	-	16.5	18.5
Amplitude Ripple (fo ± 14.9 MHz)	dB	-	0.45	1.0
Group Delay Variation (fo ± 14.9 MHz)	nsec	-	15	50


S1365 Package Dimension



Dimensions shown are nominal in millimeters

Body : Al₂O₃
Lid : Kovar, Ni Plated
Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Matching Schematic



Pin Configuration

Pin Configuration			
Input	11	Ground	6, 12
Output	5	Others	Ground

3. Typical Performance (at +25°C)

