

1. Features

- Typical 1dB Bandwidth of 10.43 MHz
- Low-Loss Filter
- Single Ended Operation
- Ceramic Surface Mount Device(SMD) Package

RoHS Compliant

Tested by SGS Testing Korea



2. Electrical Specifications

Source and Load Impedance = 50

Room Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	95.0	-
Insertion Loss	dB	-	9.1	11.0
1dB Bandwidth	MHz	10.0	10.43	-
3dB Bandwidth	MHz	-	11.26	-
40dB Bandwidth	MHz	-	14.3	14.8
Amplitude Ripple (fo ± 4.5 MHz)	dB	-	0.25	1.0
Group Delay Variation (fo ± 4.5 MHz)	nsec	-	35	70
Absolute Delay	usec	-	1.13	-
Ultimate Rejection	dB	40	45	-
Temperature Coefficient of Frequency	ppm/°C	-	-86	-

S1365 Package Dimension

Matching Schematic



L1 = 44nH, L2 = 2.7nH, L3 = 33nH

Dimensions shown are nominal in millimeters

Body : Al₂O₃

Lid : Kovar, Ni Plated

Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Pin Configuration

Pin Configuration			
Input	11	Ground	6, 12
Output	5	Others	Ground

3. Typical Performance (at +25°C)

