


# SAW Bandpass Filter 202156B



## 1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

## 2. Package Dimension



### Package : D2012


Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

| Pin Configuration |             |
|-------------------|-------------|
| 1                 | Input       |
| 5                 | Output      |
| 2, 4              | Ground      |
| 3, 6              | Case ground |

|                                                                                     |                                                                                                                                   |           |             |     |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|-----|
|  | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 202156B     |     |
|                                                                                     |                                                                                                                                   | Rev. Date | 2004-06-03  |     |
|                                                                                     |                                                                                                                                   | Rev.      | NM3020-CS02 | 1/5 |

# SAW Bandpass Filter 202156B



## 3. Specifications

Fo = 70.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

|                                        |        | Minimum | Typical | Maximum |
|----------------------------------------|--------|---------|---------|---------|
| Center Frequency                       | MHz    | 69.94   | 70.0    | 70.06   |
| Insertion Loss                         | dB     | -       | 22.5    | 25.0    |
| 1dB Bandwidth                          | MHz    | -       | 11.9    | -       |
| 3dB Bandwidth                          | MHz    | 12.0    | 12.3    | -       |
| 40dB Bandwidth                         | MHz    | -       | 13.7    | 14.0    |
| Amplitude Ripple (Fo +/- 5.7 MHz)      | dB     | -       | 0.6     | 1.0     |
| Group Delay Variation (Fo +/- 5.7 MHz) | nsec   | -       | 70      | 200     |
| Absolute Delay                         | usec   | -       | 2.74    | -       |
| Ultimate Rejection                     | dB     | 45      | 48      | -       |
| Temperature Coefficient of Frequency   | ppm/°C | -       | -94     | -       |

### Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss

|                                                                                                                     |                                                                                                                                   |           |             |     |
|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|-----|
| <br>Integrated Technology Future | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 202156B     |     |
|                                                                                                                     |                                                                                                                                   | Rev. Date | 2004-06-03  |     |
|                                                                                                                     |                                                                                                                                   | Rev.      | NM3020-CS02 | 2/5 |

# SAW Bandpass Filter 202156B



## 4. Matching Schematic

( Actual matching values may vary due to PCB layout and parasitics )



$L1 = L2 = 100 \text{ nH}$

## 5. Marking Configuration

ITF<sup>1)</sup>04A001<sup>2)</sup>  
202156B<sup>3)</sup>



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

|  |                                                                                                                                   |           |             |     |
|--|-----------------------------------------------------------------------------------------------------------------------------------|-----------|-------------|-----|
|  | <b>ITF Co., Ltd.</b><br>102-901, Bucheon Technopark 364,<br>Samjeong-Dong, Ojeong-Gu, Bucheon-City,<br>Gyeonggi-Do, Korea 421-809 | Part No.  | 202156B     |     |
|  |                                                                                                                                   | Rev. Date | 2004-06-03  |     |
|  |                                                                                                                                   | Rev.      | NM3020-CS02 | 3/5 |

# SAW Bandpass Filter 202156B



## 6. Typical Performance ( at +25°C )







**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No. 202156B

Rev. Date 2004-06-03

Rev. NM3020-CS02 4/5

# SAW Bandpass Filter 202156B



**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

|           |             |     |
|-----------|-------------|-----|
| Part No.  | 202156B     |     |
| Rev. Date | 2004-06-03  |     |
| Rev.      | NM3020-CS02 | 5/5 |