


SAW Bandpass Filter 220404B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220404B	
		Rev. Date	2007-04-19	
		Rev.	NM7017-CS01	1/5

SAW Bandpass Filter 220404B



3. Specifications

Fo = 69.8 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	69.8	-
Insertion Loss	dB	-	23.0	24.5
1dB Bandwidth	MHz	-	4.08	-
3dB Bandwidth	MHz	4.21	4.29	-
40dB Bandwidth	MHz	-	5.19	5.25
Amplitude Ripple (fo±1.92 MHz)	dB	-	0.4	1.0
Group Delay Variation (fo±1.92 MHz)	nsec	-	100	150
Absolute Delay	usec	-	4.37	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-18	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220404B	
		Rev. Date	2007-04-19	
		Rev.	NM7017-CS01	2/5

SAW Bandpass Filter 220404B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



L1=150H, L2=220nH, L3=180nH

5. Marking Configuration

ITF¹⁾ 07A001²⁾

220404B³⁾

69.8⁴⁾ -4.0M⁵⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center Frequency
- 5) 1dB-Bandwidth

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220404B	
		Rev. Date	2007-04-19	
		Rev.	NM7017-CS01	3/5

SAW Bandpass Filter 220404B







6. Typical Performance (at +25°C)



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	220404B	
Rev. Date	2007-04-19	
Rev.	NM7017-CS01	4/5

SAW Bandpass Filter 220404B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	220404B	
Rev. Date	2007-04-19	
Rev.	NM7017-CS01	5/5