


SAW Bandpass Filter 243103B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40 °C ~ 85 °C
- Electrostatics Sensitive Device (ESD)


2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters
 Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	243103B	
		Rev. Date	2013-04-26	
		Rev.	NM7035-CS02	1/5

SAW Bandpass Filter 243103B



3. Specifications

Fo = 93.75 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	93.75	-
Insertion Loss	dB	-	25.3	26.5
1dB Bandwidth	MHz	30.0	31.0	-
3dB Bandwidth	MHz	-	31.83	-
40dB Bandwidth	MHz	-	35,36	35.5
Amplitude Ripple (fo± 14.8 MHz)	dB	-	0.37	1.0
Group Delay Variation (fo± 14.8 MHz)	nsec	-	17	40
Absolute Delay	usec	-	1.09	-
Ultimate Rejection	dB	50	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	243103B	
		Rev. Date	2013-04-26	
		Rev.	NM7035-CS02	2/5

SAW Bandpass Filter 243103B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)




L1=100H, L2=100nH, C1=6pF

5. Marking Configuration

ITF¹⁾ 07A001²⁾
243103B³⁾
93.75⁴⁾ – 31.0M⁵⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center Frequency
- 5) 1dB-Bandwidth

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	243103B	
		Rev. Date	2013-04-26	
		Rev.	NM7035-CS02	3/5

SAW Bandpass Filter 243103B







6. Typical Performance (at +25°C)



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	243103B	
Rev. Date	2013-04-26	
Rev.	NM7035-CS02	4/5

SAW Bandpass Filter 243103B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	243103B	
Rev. Date	2013-04-26	
Rev.	NM7035-CS02	5/5