


SAW Bandpass Filter 270505B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)


2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters
 Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	270505B	
		Rev. Date	2009-01-05	
		Rev.	NM8085-CS01	1/5

SAW Bandpass Filter 270505B



3. Specifications

Fo = 70.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	70.0	-
Insertion Loss	dB	-	22.5	24.0
2dB Bandwidth	MHz	-	4.92	5.0
25dB Bandwidth	MHz	-	5.75	5.8
40dB Bandwidth	MHz	-	5.94	-
Amplitude Ripple (fo±2.25 MHz)	dB	-	0.4	1.0
Group Delay Variation (fo±2.25 MHz)	nsec	-	85	120
Absolute Delay	usec	-	3.97	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-18	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	270505B	
		Rev. Date	2009-01-05	
		Rev.	NM8085-CS01	2/5

SAW Bandpass Filter 270505B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)




L1 = 120nH, L2 = 150nH
L3 = 120nH, L4 = 120nH

5. Marking Configuration

ITF¹⁾ 08A001²⁾
270505B³⁾
70⁴⁾ -4.9M⁵⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center Frequency
- 5) 2dB-Bandwidth

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	270505B	
		Rev. Date	2009-01-05	
		Rev.	NM8085-CS01	3/5

SAW Bandpass Filter 270505B







6. Typical Performance (at +25°C)



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	270505B	
		Rev. Date	2009-01-05	
		Rev.	NM8085-CS01	4/5

SAW Bandpass Filter 270505B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	270505B	
Rev. Date	2009-01-05	
Rev.	NM8085-CS01	5/5