

1. Features

- Typical 1dB bandwidth of 24.6 MHz
- High attenuation
- Single Ended Operation
- Surface Mounted Package (SMD)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications

Source and Load Impedance = 50Ω

Operating Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	185.0	-
Insertion Loss	dB	-	27.8	29.5
1dB Bandwidth	MHz	24.4	24.63	-
3dB Bandwidth	MHz	-	25.16	-
40dB Bandwidth	MHz	-	27.4	27.55
Amplitude Ripple (fo ± 11.8 MHz)	dB	-	0.45	1.0
Group Delay Variation (fo ± 11.8 MHz)	nsec	-	20	50
Absolute Delay	usec	-	2.06	-
Ultimate Rejection	dB	45	50	-
Temperature Coefficient of Frequency	ppm/°C	-72		


S1365 Package Dimension



Dimensions shown are nominal in millimeters

Body : Al₂O₃
 Lid : Kovar, Ni Plated
 Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Matching Schematic



L1 = L4 = 22nH, L2 = L3 = 12nH

Pin Configuration			
Input	11	Ground	6, 12
Output	5	Others	Ground

3. Typical Performance (at +25°C)

