


# Ceramic Bandpass Filter IFD06003

## Features

- Ceramic bandpass filter
- 50Ω single-ended operation
- Surface Mounted Module Package ( 10mm × 20mm × 4.5mm )


## Package Dimensions



## Maximum Ratings

Parameter	Unit	Minimum	Typical	Maximum
Operating Temperature Range	℃	-30	25	70
Storage Temperature Range	℃	-40	25	85
Power Handling Capability	Watt	-	-	2

Electrostatics Sensitive Device (ESD)

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	IFD06003	
		Rev. Date	2014-08-26	
		Rev.	AS 01	1/4

# Ceramic Bandpass Filter IFD06003


## Specifications

Fo = 605.75MHz

	Minimum	Typical	Maximum	Unit
Center Frequency ( Fo )	-	605.75	-	MHz
Insertion Loss (605.5 ~ 606.0MHz)	-	2.0	2.5	dB
Amplitude Ripple (605.5 ~ 606.0MHz)	-	0.3	0.5	dB
Return Loss (605.5 ~ 606.0MHz)	15	18	-	dB
Relative Attenuation @1210 MHz @ 1815 MHz	40.0 30.0	45.0 35.0	- -	dB
Input/Output Impedance		50		Ohm

### Notes :

- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 3) All attenuation measurements are measured relative to insertion loss

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	IFD06003	
		Rev. Date	2014-08-26	
		Rev.	AS 01	2/4

# Ceramic Bandpass Filter IFD06003

---

## Matching Schematic

( Actual matching values may vary due to PCB layout and parasitics )




## Marking Configuration

Part No. <sup>1)</sup>


1) Part Number


\* Ink or Laser Marking available

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	IFD06003	
		Rev. Date	2014-08-26	
		Rev.	AS 01	3/4

# Ceramic Bandpass Filter IFD06003

## Typical Performance ( at 25 °C )



	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	IFD06003	
		Rev. Date	2014-08-26	
		Rev.	AS 01	4/4