

1. Features

- Typical 1dB bandwidth of 9.3 MHz
- High attenuation
- Single Ended Operation
- Dual In-line Package (DIP)

RoHS Compliant


Tested by SGS Testing Korea

2. Electrical Specifications

Source and Load Impedance = 50Ω

Room Temperature : +25°C		Minimum	Typical	Maximum
Center Frequency (fo)	MHz	-	185.0	-
Insertion Loss	dB	-	29.5	31.0
1dB Bandwidth	MHz	9.25	9.38	-
3dB Bandwidth	MHz	-	9.63	-
40dB Bandwidth	MHz	-	10.8	11.0
Amplitude Ripple (fo ± 4.51 MHz)	dB	-	0.55	1.2
Group Delay Variation (fo ± 4.51 MHz)	nsec	-	90	150
Absolute Delay	usec	-	1.88	-
Ultimate Rejection	dB	40	48	-
Temperature Coefficient of Frequency	ppm/°C ²	-	-0.03	-

D2012 Package Dimension




Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Matching Network Configuration



L1 = 68nH, L2 = 56nH, L3 = 39

C1 = 33pF

Pin Configuration

Pin Configuration			
Input	1	Ground	2,4
Output	5	Others	Ground

3. Typical Performance (at +25°C)

