


# SAW Bandpass Filter 271802B



## 1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- SMD Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)


## 2. Package Dimension



### Package : D3512

Dimensions shown are nominal in millimeters  
 Base : Fe(SPCC), Au plating over Ni plated  
 Cap : Cu & Cr Alloy, Ni Plated  
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271802B	
		Rev. Date	2007-08-16	
		Rev.	NM7027-CS01	1/5

# SAW Bandpass Filter 271802B



## 3. Specifications

Fo = 70.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	70.0	-
Insertion Loss	dB	-	26.5	27.5
1dB Bandwidth	MHz	18.1	18.12	-
3dB Bandwidth	MHz	-	18.30	-
40dB Bandwidth	MHz	-	19.0	19.02
Amplitude Ripple (Fo +/- 9.0 MHz)	dB	-	0.66	1.0
Group Delay Variation (Fo +/- 9.0 MHz)	nsec	-	75	150
Absolute Delay	usec	-	3.54	-
Ultimate Rejection	dB	45	50	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

### Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271802B	
		Rev. Date	2007-08-16	
		Rev.	NM7027-CS01	2/5

# SAW Bandpass Filter 271802B



## 4. Matching Schematic

( Actual matching values may vary due to PCB layout and parasitics )




L1 = 68nH, L2 = 82nH

## 5. Marking Configuration

ITF<sup>1)</sup> 07A001<sup>2)</sup>  
271802B<sup>3)</sup>  
70<sup>4)</sup>-18.0M<sup>5)</sup>



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center frequency
- 5) Pass-Bandwidth

 Integrated Technology Future	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271802B	
		Rev. Date	2007-08-16	
		Rev.	NM7027-CS01	3/5

# SAW Bandpass Filter 271802B



## 6. Typical Performance ( at +25°C )







**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No. 271802B

Rev. Date 2007-08-16

Rev. NM7027-CS01 4/5

# SAW Bandpass Filter 271802B



**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No.	271802B	
Rev. Date	2007-08-16	
Rev.	NM7027-CS01	5/5