


SAW Bandpass Filter 251915B



1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- SMD Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)


2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters
 Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	251915B	
		Rev. Date	2007-08-16	
		Rev.	NM7045-CS01	1/5

SAW Bandpass Filter 251915B



3. Specifications

Fo = 160.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	160.0	-
Insertion Loss	dB	-	30.8	32.0
1dB Bandwidth	MHz	19.0	19.13	-
3dB Bandwidth	MHz	-	19.34	-
50dB Bandwidth	MHz	-	20.45	20.6
Amplitude Ripple (Fo +/- 9.3 MHz)	dB	-	0.63	1.2
Group Delay Variation (Fo +/- 9.3 MHz)	nsec	-	30	100
Absolute Delay	usec	-	3.47	-
Ultimate Rejection	dB	48	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-18	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	251915B	
		Rev. Date	2007-08-16	
		Rev.	NM7045-CS01	2/5

SAW Bandpass Filter 251915B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$L1 = 39\text{nH}$, $L2 = 47\text{nH}$, $C1 = 27\text{pF}$, $C2 = 27\text{pF}$

5. Marking Configuration

ITF¹⁾07A001²⁾

251915B³⁾

160⁴⁾-19.1M⁵⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center frequency
- 5) 1dB-Bandwidth

	ITF Co., Ltd.	Part No.	251915B	
	102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Rev. Date	2007-08-16	
		Rev.	NM7045-CS01	3/5

SAW Bandpass Filter 251915B



6. Typical Performance (at +25°C)







ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No. 251915B

Rev. Date 2007-08-16

Rev. NM7045-CS01 4/5

SAW Bandpass Filter 251915B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	251915B	
Rev. Date	2007-08-16	
Rev.	NM7045-CS01	5/5