


# SAW Bandpass Filter 252652B



## 1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- SMD Package
- Maximum Storage Temperature Range : -40 °C ~ 85 °C
- Electrostatics Sensitive Device (ESD)

## 2. Package Dimension



**Package : S1365**

Dimensions shown are nominal in millimeters

Body : Al<sub>2</sub>O<sub>3</sub>

Lid : Kovar, Ni Plated

Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Pin Configuration	
11	Input
5	Output
6, 12	Ground
Other	Case ground

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	252652B	
		Rev. Date	2009-04-14	
		Rev.	NM9019-CS01	1/5

# SAW Bandpass Filter 252652B



## 3. Specifications

Fo = 115.0 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

Room temperature range : +25°C		Minimum	Typical	Maximum
Center Frequency (Fc)	MHz	-	115.0	-
Insertion Loss	dB	-	23.5	26.0
1dB Bandwidth	MHz	-	26.1	-
3dB Bandwidth	MHz	26.4	26.52	-
40dB Bandwidth	MHz	-	28.31	28.5
Amplitude Ripple (Fo +/- 12.7 MHz)	dB	-	0.5	1.0
Group Delay Variation (Fo +/- 12.7 MHz)	nsec	-	30	60
Absolute Delay	usec	-	1.58	-
Ultimate Rejection	dB	45	50	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

### Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	252652B	
		Rev. Date	2009-04-14	
		Rev.	NM9019-CS01	2/5

# SAW Bandpass Filter 252652B



## 4. Matching Schematic

( Actual matching values may vary due to PCB layout and parasitics )



$$L1 = L2 = 68\text{nH}$$

$$C1 = 7\text{pF}$$

## 5. Marking Configuration

ITF<sup>1)</sup> 08A001<sup>2)</sup>

252652B<sup>3)</sup>

115<sup>4)</sup> -26.1<sup>5)</sup>

●<sup>6)</sup>

1) Manufacturer name

2) Lot Number

3) Part Number

4) Center frequency

5) 1dB-Bandwidth



6) Pad No.1 Index

	<b>ITF Co., Ltd.</b> 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	252652B	
		Rev. Date	2009-04-14	
		Rev.	NM9019-CS01	3/5

# SAW Bandpass Filter 252652B







## 6. Typical Performance (at +25°C)



**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No.	252652B	
Rev. Date	2009-04-14	
Rev.	NM9019-CS01	4/5

# SAW Bandpass Filter 252652B



**ITF Co., Ltd.**  
 102-901, Bucheon Technopark 364,  
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,  
 Gyeonggi-Do, Korea 421-809

Part No.	252652B	
Rev. Date	2009-04-14	
Rev.	NM9019-CS01	5/5